

NON-FORESHORTENING STENT

Inventors: Geoffrey H. White, Russell Redmond

BACKGROUND OF THE INVENTION**1. Field of the Invention**

The present invention relates to an intraluminal prosthesis for implantation into a mammalian vessel, and in particular, to an intraluminal stent that is delivered in a compressed state to a specific location inside the lumen of a mammalian vessel and then deployed to an expanded state to support the vessel. The intraluminal stent is provided with a structural configuration that maintains the prosthesis at substantially the same length in both the compressed and expanded states.

2. Description of the Prior Art

Intraluminal prosthesis, such as stents, are commonly used in the repair of aneurysms, as liners for vessels, or to provide mechanical support to prevent the collapse of stenosed or occluded vessels. These stents are typically delivered in a compressed state to a specific location inside the lumen of a vessel or other tubular structures, and then deployed at that location of the lumen to an expanded state. The stent has a diameter in its expanded state which is several times larger than the diameter of the stent in its compressed state. These stents are also frequently deployed in the treatment of atherosclerotic stenosis in blood vessels, especially after percutaneous transluminal coronary angioplasty (PTCA) procedures, to improve the results of the procedure and to reduce the likelihood of restenosis.

The positioning of a stent at the desired location in the lumen of a body vessel is a critical factor that affects the performance of the stent and the success of the medical procedure. Since the region in a lumen at which the stent is to be deployed is usually very difficult for a physician to access, it is essential that the stent's deployed diameter and length be known before the physician can accurately position a stent with the correct size at the precise location. For example, since the diameter and the length of the diseased or damaged segment or region of the body vessel can vary for different body vessels, disease states, and deployment purposes, it is important that a stent having the precise diameter and length be delivered to this region for deployment.

Careful sizing of this region of the lumen of the body vessel may pose a difficult challenge for many physicians who know the exact dimensions of the body

vessel at this region, but are not certain about the stent's deployed diameter and length. This is due to a foreshortening effect which is experienced by many stents when they are expanded from their compressed state to their expanded state.

This foreshortening effect is illustrated in FIGS. 1A, 1B, 2A and 2B, which
 5 illustrate portions 20 of a stent having a mesh-like pattern made up of V-shaped struts or legs 22 and 24 connected at their apices 26. Two pairs of these V-shaped struts 22, 24 are illustrated in this portion 20 of the stent. Each of these struts 22 and 24 has a length h . FIG. 1B illustrates the portion 20 of the stent in a fully compressed state, in which the length h has a longitudinal or horizontal component l_2
 10 (see FIG. 2B), and FIG. 1A illustrates the same portion 20 of the stent in a fully expanded state, in which the length h has a longitudinal or horizontal component l_1 (see FIG. 2A). As illustrated by the imaginary lines 28 and 30 in FIGS. 1A and 1B, and in FIGS. 2A and 2B, l_1 is shorter than l_2 because the angle θ which the strut 22 assumes with respect to the horizontal axis is greater when in the expanded state, so
 15 the length of the expanded portion 20 is shorter than the length of the compressed portion 20 by a length of $2d$. This foreshortening is caused by the shortening of the longitudinal component l of the struts 22 and 24 as the stent is expanded from the compressed state to the expanded state.

This foreshortening effect is troublesome because it is not easy to determine
 20 the exact dimension of this foreshortened length $2d$. The physician must make this calculation based on the material of the stent, the body vessel being treated, and the expected diameter of the stent when properly deployed in the lumen of the body vessel. For example, the foreshortened length $2d$ will vary when the same stent is deployed in vessels having different diameters at the region of deployment.

25 In addition, there are certain body vessels that experience a change in vessel lumen diameter, anatomy or disease state along their lengths. Stents to be deployed at such vessels will need to be capable of addressing or adapting to these changes.

An example of such a body vessel are the carotid arteries. Blood is delivered from the heart to the head via the common carotid arteries. These arteries are
 30 approximately 8-10 mm in lumen diameter as they make their way along the neck up to a position just below and behind the ear. At this point, the common carotid artery branches into a 6-8 mm lumen diameter internal carotid artery, which feeds blood to the brain, and a 6-8 mm lumen diameter external carotid artery, which supplies blood to the face and scalp. Atherosclerotic lesions of the carotid artery tend to occur

around this bifurcation of the common carotid artery into the internal and external carotid arteries, so stents often need to be deployed at this bifurcation.

Another example are the iliac arteries, which have a lumen diameter of about 8-10 mm at the common iliac artery but which decrease to a lumen diameter of about 6-7 mm at the external iliac artery. The common iliac arteries experience more localized stenosis or occlusive lesion which are quite often calcific and usually require a shorter stent with greater radial strength or rigidity. More diffused atherosclerotic disease of the iliac system will commonly involve both the common and external iliac arteries, and necessitate a longer stent having increased flexibility that is suitable for deployment in the tortuous angulation experienced by the iliac system.

The femoropopliteal system similarly experiences localized and diffused stenotic lesions. In addition, the flexibility of a stent is important where deployed at locations of vessels that are affected by movements of joints, such as the hip joint or the knee joint.

The renal arteries provide yet another useful example. The initial 1 cm or so at the orifice of a renal artery is often quite firmly narrowed due to atheroma and calcification, and is relatively straight, while the remainder of the length of the renal artery is relatively curved. As a result, a stent intended for implantation at the renal arteries should be relatively rigid for its first 1.5 cm or so, and then become more flexible and compliant.

Thus, there remains a need for an intraluminal prosthesis that maintains a consistent length in both its fully compressed and fully expanded states, and in all states between its fully compressed and fully expanded states. There also remains a need for a stent which can accomodate body vessels having varying lumen diameters, different anatomies, and different disease states.

SUMMARY OF THE DISCLOSURE

In order to accomplish the objects of the present invention, there is provided a stent having a plurality of annular elements, each annular element having a compressed state and an expanded state, with each annular element having a longitudinal dimension which is smaller in the expanded state than in the compressed state. The stent also has at least one connecting member connecting adjacent annular elements, the connecting member having a longitudinal dimension

which is larger in the expanded state than in the compressed state. In one embodiment, the connecting member is straight when the annular elements are in the compressed state and in the expanded state. In another embodiment, the connecting member is straight when the annular elements are in the expanded state, and the connecting member is arcuate when the annular elements are in the compressed state.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1A is a side elevational view of a portion of a prior art stent in its expanded state;

FIG. 1B is a side elevational view of the portion of FIG. 1A in its compressed state;

FIG. 2A illustrates the longitudinal component of a strut of the stent of FIGS. 1A and 1B when the stent is in its expanded state;

FIG. 2B illustrates the longitudinal component of a strut of the stent of FIGS. 1A and 1B when the stent is in its compressed state;

FIG. 3 is a side elevational view of a portion of a stent according to one embodiment of the present invention shown in a compressed state;

FIG. 4 is a side elevational view of the portion of FIG. 3 in its expanded state;

FIG. 5 is a side elevational view of the portion of FIG. 4 in its expanded state showing the removal of certain struts and connecting members;

FIG. 6 is a side elevational view of a portion of a stent according to another embodiment of the present invention shown in a compressed state;

FIG. 7 is a side elevational view of the portion of FIG. 6 in its expanded state;

FIG. 8 is a side elevational view of a portion of a stent according to yet another embodiment of the present invention shown in a compressed state;

FIG. 9 is a side elevational view of the portion of FIG. 8 in its expanded state;

FIG. 10 is a side elevational view of a portion of a stent according to yet another embodiment of the present invention shown in a compressed state;

FIG. 11 is a side elevational view of the portion of FIG. 10 in its expanded state;

FIG. 12 is a side elevational view of a portion of a stent according to yet another embodiment of the present invention shown in a compressed state;

FIG. 13 is a side elevational view of the portion of FIG. 12 in its expanded

state;

FIG. 14 is a side elevational view of a portion of a stent according to yet another embodiment of the present invention shown in a compressed state;

5 FIG. 15 is a side elevational view of the portion of FIG. 14 in its expanded state;

FIG. 16 is a side elevational view of a portion of a stent according to yet another embodiment of the present invention shown in a compressed state; and

FIG. 17 is a side elevational view of the portion of FIG. 16 in its expanded state.

10

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

The following detailed description is of the best presently contemplated modes of carrying out the invention. This description is not to be taken in a limiting sense, but is made merely for the purpose of illustrating general principles of embodiments of the invention. The scope of the invention is best defined by the appended claims.

15 The intraluminal prosthesis according to the present invention is a stent, although the principles of the present invention are also applicable to other prosthesis such as liners and filters. The stent is delivered to a desired location in the lumen of a body vessel in a compressed state, and is then deployed by
20 expanding it to its expanded state. The stent maintains substantially the same length in both its fully compressed and fully expanded states, and in all states between these two states.

The stent according to the present invention can be a self-expanding stent, or a stent that is radially expandable by inflating a balloon or expanded by an expansion member, or a stent that is expanded by the use of radio frequency which provides
25 heat to cause the stent to change its size. The stent may also be coated with coverings of PTFE, dacron, or other biocompatible materials to form a combined stent-graft prosthesis. The vessels in which the stent of the present invention can be deployed include but are not limited to natural body vessels such as ducts, arteries,
30 trachea, veins, ureters and the esophagus, and artificial vessels such as grafts.

Stent Embodiments

FIGS. 3 and 4 illustrate a portion of a stent 40 according to one embodiment of the present invention. The stent 40 has a tubular configuration and is made up of a plurality of pairs of substantially V-shaped struts connected at their apices, and by

connecting one or more connecting members to the apices of selected pairs of V-shaped struts. In particular, the stent 40 has a plurality of pairs of alternating left struts 42 and right struts 44. Each pair of left and right struts 42, 44 is connected at an apex 46 to form a substantially V-shape for the pair. The left strut 42 is defined as being to the left of each apex 46, and the right strut 44 is defined as being to the right of each apex 46. The left struts 42 and right struts 44 are alternating since the left strut 42 of one pair of V-shaped struts is also the right strut of the adjacent pair of V-shaped struts, and the right strut 44 of one pair of V-shaped struts is also the left strut of the adjacent pair of V-shaped struts. In this manner, the alternating left and right struts 42 and 44 extend in an annular manner around the tubular stent 40 to form an annular element. Each apex 46 can be connected to another apex 46 by a connecting member 48. In this embodiment, each connecting member 48 connects adjacent apices 46 along generally the same longitudinal level (see FIG. 3). Therefore, the stent 40 resembles a tubular lattice formed by pairs of V-shaped struts 42, 44 connected to themselves and having their apices 46 connected by the connecting members 48.

The connecting members 48 are generally straight when the stent 40 is in a fully expanded configuration, and are somewhat bowed, curved, arcuate or bent when the stent 40 is in a fully compressed configuration. Each connecting member 48 lies in a generally longitudinal direction along the longitudinal axis LA of the stent 40, but at an angle A1 with respect to the longitudinal axis LA when in the fully expanded configuration (see FIG. 4).

The connecting members 48 are provided to perform two functions. First, the connecting members 48 connect pairs of apices 46. Second, the connecting members 48 function to compensate for the foreshortening experienced by the longitudinal component of each strut 42 and 44, thereby maintaining the stent 40 at substantially the same length at all times. This is accomplished by providing the connecting member 48 with a natural bias and a springy nature, which allows the connecting member 48 to shorten its longitudinal component when compressed. When allowed to expand, the connecting member 48 is biased to return to its natural or original position, which lengthens the longitudinal component of the connecting member 48 to compensate for the foreshortening experienced by the longitudinal component of each strut 42 and 44.

This compensating effect is illustrated in FIGS. 3 and 4. When the stent 40 is

in its compressed state, the connecting member 48 has a longitudinal component of L2, which is less than the longitudinal component L1 when the connecting member 48 is in its expanded state. The connecting member 48 is bowed when it is compressed for delivery, but may still be straight when laser-cut. When the stent 40 is in its compressed state, each strut 42, 44 has a longitudinal component of L4, which is greater than the longitudinal component L3 when the struts 42, 44 are in the expanded state. As the stent 40 expands radially with a pre-load, the angle A1 for each connecting member 48 decreases, thereby lengthening the longitudinal component L1 of the connecting member 48 to compensate for the gradual shortening of the longitudinal components L3 of the struts 42, 44. Thus, the difference between L2 and L1 compensates for the difference between L4 and L3 of the struts 42, 44 at both ends of the connecting member 48. The lines 70 and 72 in FIGS. 3 and 4 show that the relevant portion of the stent 40 does not experience any foreshortening and maintains a consistent length through all its states.

In addition, during expansion of the stent 40, it is possible (but not necessary) for the struts 42, 44 in one row (e.g., row 1) to rotate slightly around the longitudinal axis LA of the stent 40 with respect to the struts 42, 44 in an adjacent row (e.g., row 2), so that the struts 42, 44 in one row (e.g., row 1) would now be diagonally offset from the struts 42, 44 in an adjacent row (e.g., row 2).

When the stent 40 is in its fully expanded state, it preferably has an outer diameter that is slightly larger than the inner diameter of the region of the body vessel at which it is to be deployed. This allows the stent 40 to be securely anchored at the desired location and prevents the stent 40 from migrating away from the deployed location.

In the embodiment of FIGS. 3 and 4, all the connecting members 48 are oriented at the same angle and direction throughout the length of the stent 40. Such an orientation would provide the overall structure of the stent 40 with a spiral element at certain intervals, which would enhance the flexibility of the stent 40 at selected locations. In this regard, it is useful for the stent 40 to be provided with varying flexibility or rigidity at different portions or segments along its length to facilitate deployment in body vessels that require such varying flexibility or rigidity, such as curved or angulated body vessels.

The flexibility of the stent 40 can be further varied by omitting one or more connecting members 48 and/or struts 42, 44, such as illustrated in FIG. 5. For

example, the connecting member 48x and the strut 42x in FIG. 4 is omitted in FIG. 5, with the stent in FIG. 5 being otherwise identical to the stent in FIG. 4. Omitting connecting members 48 and struts 42, 44 will create "gaps" at one or more locations along the stent 40. These locations can be anywhere along the length and/or the circumference of the stent 40. In addition, varying degrees of flexibility in the stent 40 can be accomplished by varying the patterns of these gaps. A non-limiting example would be to provide a substantially spiral pattern of omitted struts 42, 44 and/or connecting members 48.

A number of materials can be used for both the stent 40 and its struts 42, 44 and connecting members 48, depending on its method of deployment. If used as a self-expanding stent, the stent 40 (including its struts 42, 44 and connecting members 48) is preferably made of a shape memory superelastic metal alloy such as Nitinol, which has the unusual property of "mechanical" memory and trainability. This alloy can be formed into a first predetermined shape above a transition temperature range. The alloy may be plastically deformed into a second shape below the transition temperature range, but the alloy will completely recover to its original (first predetermined) shape when raised back above the transition temperature range. The Nitinol preferably has a composition of about 50% nickel and about 50% titanium. The properties of shape memory alloys such as Nitinol and their use in stents have been well-documented in the literature, and reference can be made to the article by T.W. Duerig, A.R. Pelton and D. Stockel entitled "The Use of Superelasticity in Medicine", a copy of which is attached hereto and specifically incorporated into this specification by specific reference thereto as though fully set forth herein.

Although the connecting members 48 have been described above as having the same material as the struts 42, 44, it is possible to provide the connecting members 48 with a different material without departing from the spirit and scope of the present invention. Such a material should be springy in nature and should allow the connecting members 48 to be compressed and expanded in the longitudinal direction to compensate for the foreshortening experienced by the struts 42 and 44. Non-limiting examples of such materials can include any of the materials described above for the stent 40.

FIGS. 6 and 7 illustrate a portion of a stent 40a according to another embodiment of the present invention. The stent 40a is essentially the same as the

stent 40 in FIGS. 3 and 4, except that alternating rows of the connecting members 48a are oriented at opposite angles and directions throughout the length of the stent 40a. Otherwise, the other elements of the stent 40a are the same as the stent 40, and have the same numeral designations except that an "a" has been added.

5 FIGS. 8 and 9 illustrate a portion of a stent 40b according to another embodiment of the present invention. The stent 40b is essentially the same as the stent 40 in FIGS. 3 and 4, except that the connecting members 48b are connected to apices 46b that are diagonally disposed (i.e., at an angle) with respect to each other along the longitudinal axis LA. Otherwise, the other elements of the stent 40b are
10 the same as the stent 40, and have the same numeral designations except that a "b" has been added.

The designs of the stents 40a and 40b provide different types and regions of flexibility (when compared with the stent 40) that may be useful in certain specific applications.

15 FIGS. 10 and 11 illustrate a portion of a stent 40c according to yet another embodiment of the present invention. The stent 40c is essentially the same as the stent 40 in FIGS. 3 and 4, except that each of two adjacent connecting members 48c and 48d has a first end that is connected to a separate apex 46c in one row (e.g., row 2), and a second end that is connected to a single apex 46d in an adjacent row
20 (e.g., row 1). In addition, when viewed along the same row, each of two circumferentially adjacent apices will be connected to one connecting member, followed by the next circumferentially adjacent apex being connected to two connecting members, and then followed by each of the next two circumferentially adjacent apices being connected to one connecting member, and so on in the same
25 pattern. Otherwise, the other elements of the stent 40c are the same as the stent 40, and have the same numeral designations except that a "c" has been added. Thus, the two connecting members 48c and 48d operate as double-struts, and are effective in providing the portion of the stent 40c with added rigidity.

30 FIGS. 12 and 13 illustrate a portion of a stent 40e according to yet another embodiment of the present invention. The stent 40e is essentially the same as the stent 40 in FIGS. 3 and 4, except that each connecting member 48e is completely straight in both the compressed and the expanded states. Each connecting member 48e lies at an angle A2 with respect to the longitudinal axis LA when in the fully compressed configuration (see FIG. 12), and at an angle A3 with respect to the

longitudinal axis LA when in the fully expanded configuration (see FIG. 13), with the angle A2 being greater than the angle A3. The connecting members 48e are also provided with a natural bias and a springy nature, which allows the connecting member 48e to shorten its longitudinal component, and hence increases its angle from A3 to A2, when compressed. When allowed to expand, the connecting member 48e is biased to return to its natural or original position, which lengthens the longitudinal component of the connecting member 48, and hence decreases its angle from A2 to A3, to compensate for the foreshortening experienced by the longitudinal component of each strut 42e and 44e. If the material used for the connecting members 48e is Nitinol, the natural bias or spring nature of the connecting members 48e can be created when the entire stent 40e is being heat-treated to "set" the shape memory of the Nitinol material prior to compression, as explained in greater detail hereinbelow.

This compensating effect is illustrated in FIGS. 12 and 13. When the stent 40e is in its compressed state, the connecting member 48e has a longitudinal component of L22, which is less than the longitudinal component L11 when the connecting member 48e is in its expanded state. The connecting member 48e assumes a greater angle A2 with respect to the longitudinal axis LA when in the compressed state. When the stent 40e is in its compressed state, each strut 42e, 44e has a longitudinal component of L44, which is greater than the longitudinal component L33 when the struts 42e, 44e are in the expanded state. As the stent 40e expands radially, the angle A2 for each connecting member 48e decreases, thereby lengthening the longitudinal component L11 of the connecting member 48e to compensate for the gradual shortening of the longitudinal components L33 of the struts 42e, 44e. Thus, the difference between L22 and L11 compensates for the difference between L44 and L33 of the struts 42e, 44e at both ends of the connecting member 48e. The lines 70e and 72e in FIGS. 12 and 13 show that the relevant portion of the stent 40e does not experience any foreshortening and maintains a consistent length through all its states.

In addition, during expansion of the stent 40e, the struts 42e, 44e in one row (e.g., row 1) would effectively rotate slightly around the longitudinal axis LA of the stent 40e with respect to the struts 42e, 44e in an adjacent row (e.g., row 2), so that the struts 42e, 44e in one row (e.g., row 1) would now be diagonally offset from the struts 42e, 44e in an adjacent row (e.g., row 2). In this manner, the entire length of

the stent 40e can experience a helical twist or rotation (when one compares one end of the stent 40e with the opposing end of the stent 40e) when the stent 40e is expanded from the fully compressed configuration to the fully expanded configuration.

5 FIGS. 14 and 15 illustrate a portion of a stent 40f according to another embodiment of the present invention. The stent 40f is essentially the same as the stent 40a in FIGS. 6 and 7, except that each connecting member 48f is completely straight in both the compressed and the expanded states. Thus, the stent 40f in FIGS. 14 and 15 combines the principles of the stents 40a and 40e. In other words, 10 alternating rows of the connecting members 48f are oriented at opposite angles and directions throughout the length of the stent 40f, and each connecting member 48f is completely straight in both the compressed and the expanded states. Otherwise, the other elements of the stent 40f are the same as the stent 40a, and have the same numeral designations except that an "f" has been used instead of an "a".

15 FIGS. 16 and 17 illustrate a portion of a stent 40g according to yet another embodiment of the present invention. The stent 40g is essentially the same as the stent 40c in FIGS. 10 and 11, except that each connecting member 48g is completely straight in both the compressed and the expanded states. Thus, the stent 40g in FIGS. 16 and 17 combines the principles of the stents 40c and 40e. In 20 other words, each of two adjacent connecting members 48g and 48h has a first end that is connected to a separate apex 46g in one row (e.g., row 2), and a second end that is connected to a single apex 46h in an adjacent row (e.g., row 1); and each connecting member 48g, 48h is completely straight in both the compressed and the expanded states. In addition, when viewed along the same row, each of two 25 circumferentially adjacent apices will be connected to one connecting member, followed by the next circumferentially adjacent apex being connected to two connecting members, and then followed by each of the next two circumferentially adjacent apices being connected to one connecting member, and so on in the same pattern. Otherwise, the other elements of the stent 40g are the same as the stent 30 40c, and have the same numeral designations except that a "g" or "h" has been used instead of a "c" or "d".

Methods of Manufacture

The stent 40 can be made from one of a number of methods, depending on the material of the stent 40 and the desired nature of deployment. The methods described below apply to the stents 40a-40c and 40e-40g as well.

In a non-limiting first preferred method, the stent 40 is fabricated from a solid Nitinol tube with dimensions that are identical to the stent 40 when it is in the fully compressed state. The pattern of the stent 40 (i.e., its struts 42, 44 and connecting members 48) is programmed into a computer-guided laser cutter or lathe which cuts out the segments between the struts 42, 44 and the connecting members 48 in a manner which closely controls the outside diameter and wall thickness of the stent 40.

After the cutting step, the stent 40 is progressively expanded until it reaches its fully expanded state. The expansion can be performed by an internal expansion fixture, although other expansion apparatus and methods can be used without departing from the spirit and scope of the present invention. The overall length of the stent 40 is preferably consistently maintained throughout the expansion of the stent 40 from its fully compressed to its fully expanded states.

Once the stent 40 has been expanded to its fully expanded state, it is heat-treated to "set" the shape memory of the Nitinol material to the fully expanded dimensions. The stent 40 is then cleaned and electro-polished.

The next step is to compress the stent 40 again into a dimension which allows for delivery into a vessel, either through percutaneous delivery or through minimally invasive surgical procedures. Specifically, the stent 40 must be compressed into a smaller state so that it can be delivered by a delivery device to the desired location of the vessel. Any conventional delivery device could be used, such as but not limited to a tube, catheter, or sheath. The compression is accomplished at low temperatures and involves radial and longitudinal compression to maintain the desired (same) length. This compression is accomplished by cooling the stent 40 to a low temperature, for example, zero degrees Celcius, and while maintaining this temperature, compressing the stent 40 to allow the stent 40 to be inserted inside the delivery device. Once inserted inside the delivery device, the stent 40 is held by the delivery device in the compressed state at room temperature.

While certain methods of manufacture have been described above, it will be appreciated by those skilled in the art that other methods of manufacture can be

utilized without departing from the spirit and scope of the present invention.

Deployment Methods

5 The stent 40 can be deployed by a number of delivery systems and delivery methods. These delivery systems and methods will vary depending on whether the stent 40 is expanded by self-expansion, radial expansion forces, or radio frequency.

10 While the description above refers to particular embodiments of the present invention, it will be understood that many modifications may be made without departing from the spirit thereof. The accompanying claims are intended to cover such modifications as would fall within the true scope and spirit of the present invention.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201